

Global SunGate Series



Solid Reliability For A Wide Range Of Applications

For home or business, Global's SunGate window films offer outstanding solar control to reduce heating and fading, add privacy and enhance the building's appearance – all at an exceptional value.

- Choose from a full range of solar energy performance options
- Available in widths from 36" up to 72" which means no splicing on most glass
- A durable scratch resistant coating is standard on all SunGate films
- All SunGate films offer excellent solar heat rejection
- All versions well suited for various residential and commercial applications
- Strong factory backed warranty coverage

SunGate Crystal

Sophisticated multi-layered laminate construction provides the lowest visual light reflectivity of any Global film. Crystal films are ideal for demanding residential applications where a subtle appearance and low-reflectivity are major concerns.

	SOLAR ENERGY			VISIBLE LIGHT			UVR	TSER	GR
	T	A	R	T	R	R			
				Int		Ext			
Crystal 50	44	48	8	52	10	9	99	43	42
Crystal 35	33	60	7	42	9	8	99	50	53
Crystal 20	14	72	14	21	14	13	99	65	77

SunGate Alox

Manufactured using a unique oxidizing procedure that reduces reflectivity inside and out. These films are an excellent "all-around" choice with outstanding characteristics covering a broad spectrum of needs.

	SOLAR ENERGY			VISIBLE LIGHT			UVR	TSER	GR
	T	A	R	T	R	R			
				Int		Ext			
Alox 50	45	44	11	55	9	10	99	43	39
Alox 35	27	55	18	36	11	15	99	57	60
Alox 20	18	71	11	25	10	10	99	61	72



GRAPH LEGEND	
T	= Transmitted
A	= Absorbed
R	= Reflected
UVR	= Ultraviolet Rejected
TSER	= Total Solar Energy Rejected
GR	= Glare Reduction